

# VEHICLE WRAP WITHOUT THE HASSLE

RI-JET THE SMART CHOICE FOR VEHICLE WRAP PROFESSIONALS

AS SEEN AT



*Outstanding colour print results*

*Easy repositioning capability*

*Bubble free Airflow technology*

## FEATURES INCLUDE

- Ideal using UV, solvent & eco solvent inks
- Initial low tack – long-term high tack
- Can handle the harsh Aussie climate
- Manufactured in the United Kingdom
- Excellent value for money



exclusive to Jetmark

Using Ri-Jet, Ritrama's Repositionable Vehicle Wrap with Airflow, is the ideal way to apply high impact fleet branding and decoration which is durable, cost effective and eye-catching.

To ensure a highly professional finish the Wrap has a specially formulated adhesive designed to avoid the formation of unsightly creases and bubbles. It has a very low initial tack allowing easy repositioning during application. After a short while the adhesive builds to a high tack permanent state, ensuring long-term security during the life cycle of the media.

In addition, the special Airflow pattern in the liner allows air entrapped during application to be easily squeezed out, allowing a faster and bubble free application, and without leaving the liner texture on the face material. Made in the UK, Ri-Jet is a carefully manufactured under strict parameters to ensure consistency of quality, so when you use Ri-Jet you can be sure it will perform to the high standards you expect. A matching laminate is available and recommended to protect the print surface for longer life. Ritrama Repositionable Vehicle Wrap with Airflow really is the smart choice for vehicle wrap professionals.



P 1800 538 627 W [jetmark.com.au](http://jetmark.com.au) E [sales@jetmark.com.au](mailto:sales@jetmark.com.au)

E & O.E. Prices are gst exclusive.  
© Copyright Jetmark Signage Supplies



FABRICS, MEDIA, VINYL & LAMINATES

DIGITAL CAST SELF ADHESIVE VINYL

CODE

**Ritrama White Gloss**  
Ri-Jet 50 Cast Gloss White Airflow  
Repositionable Vehicle Wrap Kit

1520mm x 50m	054-1027
1370mm x 10m	054-1022-a
1370mm x 20m	054-1022-b
1370mm x 50m	054-1022-c

✔ Suitable for use with solvent, eco-solvent, and uv inks ✔ Ideal for vehicle wrap and outdoor promotional graphics.

✔ Ritrama Ri-Jet 50 Cast Gloss White Repositionable is a professional level Vehicle Wrap with Airflow technology and excellent blackout ✔ The face material provides excellent print quality ✔ The adhesive, features a very low initial tack allowing for easy repositioning during application with high final adhesion value and good water resistance ✔ Provides high adhesion on a wide variety of substrates inc. glass, ABS, PS, PVC ✔ Made in the UK ✔ Matching Laminate - 30 Flexilam.

RI-JET VEHICLE WRAP		50 CAST GLOSS WHITE	30 FLEXILAM CAST CLEAR LAM
<b>Face Material</b>	Type	Cast vinyl film	Soft vinyl
	Colour and Finish	Gloss white	Gloss clear Cast
	Weight	70g/m <sup>2</sup> ±10% ISO-536	40g/m <sup>2</sup> ±10% ISO-536
	Thickness	50µ ±10% ISO 534-80	30µ ±10% ISO 534-80
<b>Adhesive</b>	Solvent based repositionable permanent adhesive, featuring low initial tack with high final adhesion value, good water resistance. High adhesion on a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP). The grey pigmentation of the adhesive gives to the material excellent coverage performances.		Solvent based acrylic permanent adhesive featuring high cohesion and good water resistance. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).
	Reference	ASP33 repositionable permanent Grey	ASP26 permanent
	Type	Repositionable permanent	Acrylic permanent
	Min. Appl. Temp.	+10°C	+10°C
	Service Temp.	-20°C/+120°C	-20°C/+130°C
	Shear	Very High	High
	Tack	3 N/inch <sup>2</sup>	Medium N/inch <sup>2</sup>
	Final Adhesion	15 N/inch	High N/inch
<b>Liner</b>	Type	Embossed PE coated kraft paper Airflow texture	One side siliconised clay coated kraft
	Colour and Finish	White	White
	Weight	135 g/m <sup>2</sup> ±10% PP-032 - ISO 536	140 g/m <sup>2</sup> ±10% PP-032 - ISO 536
	Thickness	150µ ±10% ISO 534	150µ ±10% ISO 534
	Transparency	n.a. % DIN 53 147-64	n.a. % DIN 53 147-64
<b>Applications</b>	Ideal for vehicle applications (for flat sided including buses, trams and taxis and for corrugated surfaces and vehicle wrapping). Also suitable for window graphics, outdoor and indoor posters, billboards and signs.		Ultra thin overlamination film ideal for vehicle wraps and also for laminating UV cure ink-jet printed images
<b>Printing Methods</b>	The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.		Not printable. Testing for suitability between media, printers and inks is always recommended prior to use.
<b>Shelf life</b>	36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following storage conditions: <ul style="list-style-type: none"> <li>• This material must be stored at a temperature of 22°C ± 2°C and 50 ±5% of Relative Humidity.</li> <li>• Storage area must be dry and clean.</li> <li>• Keep the material in the original packaging when not used in order to protect it from dust and contamination.</li> <li>• Do not expose to direct sunlight or heat sources All Ritrama products are subject to strict manufacturing controls to guarantee good quality products.</li> </ul>		



The above information is based on research believed to be reliable by Ritrama, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

